

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NK52510R10
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-754-3131
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NK525-10R10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.219 Inches Minimum
Fastener Length:	0.625 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.375 Inches Nominal
Head Height:	0.094 Inches Nominal
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.025 Inches Nominal
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NK525-10R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.