

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NK52510R10 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-754-3131 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NK525-10R10 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.219 Inches Minimum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.375 Inches Nominal |
| Head Height: | 0.094 Inches Nominal |
| Extended Washer Diameter: | 0.437 Inches Nominal |
| Extended Washer Thickness: | 0.025 Inches Nominal |
| Locking Feature: | Patch Threads Or Strip Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall Or Zinc Overall |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NK525-10R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.