

P/N NK525-10R11

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NK52510R11

Minimum Qty (MOQ): 25 EA

NSN: 5305-00-944-7550

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NK525-10R11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.687 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.375 Inches Nominal
Head Height:	0.094 Inches Nominal
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.025 Inches Nominal
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NK525-10R11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NK525-10R11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NK525-10R11 and selecting the quantity you want then click "add to cart".