

**Description**

Fastener Length: 5/8", Thread: 10-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NK52510R11
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-944-7550
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NK525-10R11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.406 Inches Minimum
<b>Fastener Length:</b>	0.687 Inches Nominal
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.375 Inches Nominal
<b>Head Height:</b>	0.094 Inches Nominal
<b>Extended Washer Diameter:</b>	0.437 Inches Nominal
<b>Extended Washer Thickness:</b>	0.025 Inches Nominal
<b>Locking Feature:</b>	Pellet Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Zinc Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NK525-10R11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.