

P/N NK525-10R9

Description

Length: 37/64", Thread: 10-32, Thread Length: 7/16", NK525 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NK52510R9


Minimum Qty (MOQ): 20

NSN: 5305-00-042-3915

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













P/N NK525-10R9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.593 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.375 Inches Nominal
Head Height:	0.089 Inches Minimum And 0.099 Inches Maximum
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.020 Inches Minimum And 0.030 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NK525-10R9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NK525-10R9 and selecting the quantity you