

**Description**

Fastener Length: 25/32", Thread: 10-32, Thread Length: 29/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NK525D10R12         |
| Minimum Qty (MOQ):      | 10                  |
| NSN:                    | 5305-00-849-8055    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013680, Alum Screws |



\* See page 2 for technical characteristics

## P/N NK525D10R12 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.297 Inches Minimum And 0.453 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.719 Inches Minimum And 0.781 Inches Maximum  |
| <b>Head Style:</b>  | Round Extended Washer  |
| <b>Head Diameter:</b>                                       | 0.365 Inches Minimum And 0.385 Inches Maximum  |
| <b>Head Height:</b>   | 0.089 Inches Minimum And 0.099 Inches Maximum  |
| <b>Extended Washer Diameter:</b>                            | 0.427 Inches Minimum And 0.447 Inches Maximum  |
| <b>Extended Washer Thickness:</b>                           | 0.025 Inches Minimum And 0.030 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 62000 Pounds Per Square Inch   |
| <b>Screw Material:</b>                                      | Aluminum Alloy 2024  |
| <b>Screw Material Document And Classification:</b>          | Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses  |
| <b>Thread Series Designator:</b>                            | Unf  |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D10R12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.