

P/N NK525D832R14

Military-Fasteners.com

Description

Fastener Length: 7/8", Thread: 8-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NK525D832R14 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-903-7688 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NK525D832R14 Specifications

| Thread Class: | 2a |
|----------------------------|------------------------------|
| Thread Direction: | Right-hand |
| Thread Length: | 0.407 Inches Minimum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Diameter: | 0.312 Inches Nominal |
| Head Height: | 0.087 Inches Nominal |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.023 Inches Nominal |
| Locking Feature: | Pellet Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Material: | Aluminum Alloy Overall |
| Surface Treatment: | Anodize Overall |
| Thread Series Designator: | Unc |

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D832R14</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.