

Description

Fastener Length: 15/32", Thread: 8-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NK525D832R7
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-619-4774
National Motor Freight:	013680, Alum Screws

NO IMAGE
AVAILABLE

P/N NK525D832R7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Fastener Length:	0.406 Inches Minimum And 0.469 Inches Maximum
Head Style:	Button
Head Diameter:	0.375 Inches Nominal
Head Height:	0.087 Inches Nominal
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Anodize Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D832R7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.