

**Description**

Fastener Length: 15/32", Thread: 8-32, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NK525D832R7
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-619-4774
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N NK525D832R7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.344 Inches Minimum And 0.406 Inches Maximum
<b>Fastener Length:</b>	0.406 Inches Minimum And 0.469 Inches Maximum
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.375 Inches Nominal
<b>Head Height:</b>	0.087 Inches Nominal
<b>Locking Feature:</b>	Pellet Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D832R7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.