

Description

Fastener Length: 17/32", Thread: 8-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NK525D832R8 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-655-5850 |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE
AVAILABLE

P/N NK525D832R8 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.334 Inches Minimum And 0.416 Inches Maximum |
| Fastener Length: | 0.469 Inches Minimum And 0.531 Inches Maximum |
| Head Style: | Button |
| Head Diameter: | 0.375 Inches Nominal |
| Head Height: | 0.082 Inches Minimum And 0.092 Inches Maximum |
| Locking Feature: | Pellet Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-354 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Thread Series Designator: | Unc |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D832R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.