

**Description**

Fastener Length: 5/8", Thread: 8-36, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NK525D8R10
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-052-1560
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N NK525D8R10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.407 Inches Minimum
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.375 Inches Nominal
<b>Head Height:</b>	0.087 Inches Nominal
<b>Locking Feature:</b>	Patch Threads Or Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s:helicopter, Green Giant H-3; Helicopter, Sea King H-3; Helicopter, Super Jolly H-53
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D8R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.