



Military-Fasteners.com

P/N NK525D8R10

Description

Fastener Length: 5/8", Thread: 8-36, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NK525D8R10
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-052-1560
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N NK525D8R10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	0.625 Inches Nominal
Head Style:	Button
Head Diameter:	0.375 Inches Nominal
Head Height:	0.087 Inches Nominal
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:helicopter, Green Giant H-3; Helicopter, Sea King H-3; Helicopter, Super Jolly H-53
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NK525D8R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.