

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	OSB100T0504
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-020-9759
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N OSB100-T05-04 Specifications

Fastener Length:	Any Acceptable
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.178 Inches Minimum And 0.180 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	Any Acceptable
Expansion Device:	Serrated Stem-type W
Grip Length:	0.219 Inches Minimum And 0.282 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Serrated Stem Coated With Unbrightened Cyanide
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
Material:	Steel Comp 8740 Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-f-81177 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-f-81177,ty 1 Cl 3 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSB100-T05-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.