

Description

Fastener Length: 31/64", OSB100-T series rivets

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	OSB100T0605
Minimum Qty (MOQ):	1
NSN:	5320-01-100-1174
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N OSB100-T06-05 Specifications

Fastener Length:	0.490 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.213 Inches Minimum And 0.215 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.386 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.281 Inches Minimum And 0.345 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Mechanical Lock Or Steel Mechanical Lock
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
Material:	Steel Comp 8740 Stem
Surface Treatment:	Cadmium Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSB100-T06-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.