

Description

OSB100-T series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | OSB100T0614 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5320-01-037-6200 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N OSB100-T06-14 Specifications

| | |
|---|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.213 Inches Minimum And 0.215 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.337 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.906 Inches Minimum And 0.970 Inches Maximum |
| Shear Strength: | 3450 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Comp 4027 Body Or Steel Comp 4037 Body |
| Material: | Steel Comp 8740 Stem |
| Material: | Steel Mechanical Lock |
| Surface Treatment: | Cadmium Body |
| Surface Treatment: | Cadmium Mechanical Lock |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Mil-f-81177 Mil Spec Single Treatment Response Body |
| Surface Treatment Document And Classification: | Mil-f-81177 Mil Spec Single Treatment Response Mechanical Lock |
| Surface Treatment Document And Classification: | Mil-f-81177,unbrightened Cyanide Mil Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSB100-T06-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.