

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	OSB100T0615
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-037-6201
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N OSB100-T06-15 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.213 Inches Minimum And 0.215 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.337 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.844 Inches Minimum And 0.907 Inches Maximum
Shear Strength:	3450 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4027 Body Or Steel Comp 4037 Body
Material:	Steel Comp 8740 Stem
Material:	Steel Mechanical Lock
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Mechanical Lock
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-f-81177 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Mil-f-81177 Mil Spec Single Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Mil-f-81177,unbrightened Cyanide Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSB100-T06-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.