

**Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	OSB100T0615
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-037-6201
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N OSB100-T06-15 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.213 Inches Minimum And 0.215 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.337 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.844 Inches Minimum And 0.907 Inches Maximum
<b>Shear Strength:</b>	3450 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4027 Body Or Steel Comp 4037 Body
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material:</b>	Steel Mechanical Lock
<b>Surface Treatment:</b>	Cadmium Body
<b>Surface Treatment:</b>	Cadmium Mechanical Lock
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-f-81177 Mil Spec Single Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Mil-f-81177 Mil Spec Single Treatment Response Mechanical Lock
<b>Surface Treatment Document And Classification:</b>	Mil-f-81177,unbrightened Cyanide Mil Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSB100-T06-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.