

P/N OSB100-T5-6

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: OSB100T56

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-100-1172

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



^{*} See page 2 for technical characteristics

P/N OSB100-T5-6 Specifications

Fastener Length:	0.530 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.178 Inches Minimum And 0.180 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.333 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.344 Inches Minimum And 0.407 Inches Maximum
Shear Strength:	2340 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Mechanical Lock Or Steel Mechanical Lock
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Aisi 4027 National Spec 1st Material Response Sleeve Or Aisi 4037 National Spec 2nd Material Response Sleeve
Material Document And Classification:	Aisi 8740 National Spec Single Material Response Stem
Material Document And Classification:	Ams5737 Assn Std Single Material Response Mechanical Lock
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-f-81177 Mil Spec Single Treatment Response Overall
Supplementary Features:	Stem Cadmium Coat Unbrightened Cyanide
Specification/standard Data:	81755-c9502 Manufacturers Specification Control And 29666-osb100-t Manufacturers Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/OSB100-T5-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.