

**Description**

Fastener Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	OSMLS100B0603
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-177-1690
Schedule B:	7616.10.3000
ECCN:	EAR99

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE  
AVAILABLE

## P/N OSMLS100-B06-03 Specifications

<b>Fastener Length:</b>	0.350 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.201 Inches Nominal
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.125 Inches Minimum And 0.188 Inches Maximum
<b>Minimum Tensile Strength:</b>	715 Pounds Per Square Inch
<b>Shear Strength:</b>	1165 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Oversize Dia,for Repair/replacement Of Nas 1921b06-03
<b>Material:</b>	Aluminum Alloy Overall
<b>Surface Treatment:</b>	Anodize Expander
<b>Test Data Document:</b>	29666-osmls100 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSMLS100-B06-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.