

Description

Fastener Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	OSMLS100B0603
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-177-1690
Schedule B:	7616.10.3000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N OSMLS100-B06-03 Specifications

Fastener Length:	0.350 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.201 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Minimum And 0.188 Inches Maximum
Minimum Tensile Strength:	715 Pounds Per Square Inch
Shear Strength:	1165 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Oversize Dia,for Repair/replacement Of Nas 1921b06-03
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Expander
Test Data Document:	29666-osmls100 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/OSMLS100-B06-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.