

**Description**

Thread Size: 1/2", Length: 2-3/8", Head Width: 3/4", Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	P25000
Minimum Qty (MOQ):	1 EA
NSN:	5930-00-070-8196
National Motor Freight:	061300, Circuit Breaker / Switch Noi



\* See page 2 for technical characteristics

# P/N P25000 Specifications

Thread Class:	2a Single Threaded Bushing
Thread Length:	0.438 Inches Nominal Single Threaded Bushing
Overall Length:	2.437 Inches Maximum
Body Diameter:	0.312 Inches Nominal
Body Length:	1.032 Inches Nominal
Bulb Length:	0.594 Inches Nominal
Bulb Diameter:	0.312 Inches Nominal
Temp Sensing Element Type:	Bulb
Width Across Flats:	0.750 Inches Nominal
Operating Temp Rating:	-65.0 Deg Fahrenheit Minimum And 800.0 Deg Fahrenheit Maximum
Mounting Method:	Threaded Bushing
Features Provided:	Hermetically Sealed Case
Thread Quantity Per Inch:	20 Single Threaded Bushing
Contact Action Stimulus:	Increase
Nominal Thread Size:	0.500 Inches Single Threaded Bushing
Nonpile-up Contact Arrangement:	1 Pole, Single Throw, Both Positions Maintained
Terminal Type:	Connector, Receptacle
Contact Load Current Rating:	1.5 Amperes Resistive Load First Voltage And 500.0 Milliamperes Inductive Load First Voltage
Contact Load Current Rating:	1.5 Amperes Resistive Load Second Voltage And 500.0 Milliamperes Inductive Load Second Voltage
Contact Adjustability:	Deactuation Point Not Adjustable And Actuation Point Adjustable, Preset
Contact Adjustment Range:	-20.00/+600.00 Actuation Point Degrees Fahrenheit
Contact Adjustment Range:	-20.00 To 600.00 Actuation Point Degrees Fahrenheit
Contact Stimulus Rating:	122.00 Actuation Point Minimum Degrees Fahrenheit And 128.00 Actuation Point Maximum Degrees Fahrenheit And 1.00 Deactuation Point Nominal Degrees Fahrenheit
Contact Voltage Rating In Volts:	115.0 Ac At Sea Level First Voltage
Contact Voltage Rating In Volts:	28.0 Dc At Sea Level Second Voltage
Media For Which Designed:	Gas Or Liquid
Style Designator:	Cylindrical W/flange
Thread Series Designator:	Unf Single Threaded Bushing

## How to Order

Order this bearing from our inventory online by visiting <https://military-fasteners.com/bearings/bearings/P25000> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.