

P/N PBF1166-4-11

Description

Fastener Length: 1-3/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: PBF1166411

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-054-6264

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N PBF1166-4-11 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.378 Inches Minimum And 0.428 Inches Maximum |
| Fastener Length: | 1.076 Inches Minimum And 1.106 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.350 Inches Minimum And 0.399 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 49.0 Rockwell C Maximum Overall |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp H11 Overall |
| Material Document And Classification: | Ams 6487 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/PBF1166-4-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.