

Description

Fastener Length: 4-1/32", Thread: 3/4-16, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PBF15931246
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-368-7317
Schedule B:	7508.90.5000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N PBF1593-12-46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.149 Inches Nominal
Fastener Length:	4.009 Inches Minimum And 4.039 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.600 Inches Nominal
Extended Washer Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Extended Washer Thickness:	0.108 Inches Nominal
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Head Minor Diameter:	0.797 Inches Minimum And 0.812 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.875 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	18000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Special Features:	Centerdrill In Point End At Manufacturer's Option On Dash Number 12 And 14 Sizes
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PBF1593-12-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.