

## P/N PBF1593-14-26

## **Description**

Fastener Length: 2-15/16", Thread: 7/8-14, Thread Length: 1-5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: PBF15931426

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-455-5692

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N PBF1593-14-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.317 Inches Nominal
Fastener Length:	2.942 Inches Nominal
Head Style:	Spline Extended Washer
Head Height:	0.700 Inches Nominal
Extended Washer Diameter:	1.615 Inches Minimum And 1.625 Inches Maximum
Extended Washer Thickness:	0.116 Inches Minimum And 0.136 Inches Maximum
Grip Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
Head Minor Diameter:	0.923 Inches Minimum And 0.938 Inches Maximum
lii End Item Identification:	C-17 Globemaster lii
Nominal Thread Diameter:	0.8750 Inches
Grip Length:	1.625 Inches Nominal
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:	Nickel Alloy 718 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/PBF1593-14-26">https://military-fasteners.com/bolts/machine+bolts/PBF1593-14-26</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.