

**Description**

Fastener Length: 3-37/64", Thread: 7/8-14, Thread Length: 1-5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	PBF15931436
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-366-1129
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N PBF1593-14-36 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.317 Inches Nominal
<b>Fastener Length:</b>	3.552 Inches Minimum And 3.582 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.700 Inches Nominal
<b>Extended Washer Diameter:</b>	1.615 Inches Minimum And 1.625 Inches Maximum
<b>Extended Washer Thickness:</b>	0.126 Inches Nominal
<b>Grip Diameter:</b>	0.8730 Inches Minimum And 0.8740 Inches Maximum
<b>Head Minor Diameter:</b>	0.923 Inches Minimum And 0.938 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.875 Inches
<b>Grip Length:</b>	2.250 Inches Nominal
<b>Thread Quantity Per Inch:</b>	14
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
<b>Special Features:</b>	Centerdrill In Point End At Manufacturer's Option On Dash Number 12 And 14 Sizes
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams5662 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PBF1593-14-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.