



Military-Fasteners.com

P/N PBF1593-14-36

Description

Fastener Length: 3-37/64", Thread: 7/8-14, Thread Length: 1-5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PBF15931436
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-366-1129
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N PBF1593-14-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.317 Inches Nominal
Fastener Length:	3.552 Inches Minimum And 3.582 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.700 Inches Nominal
Extended Washer Diameter:	1.615 Inches Minimum And 1.625 Inches Maximum
Extended Washer Thickness:	0.126 Inches Nominal
Grip Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
Head Minor Diameter:	0.923 Inches Minimum And 0.938 Inches Maximum
Nominal Thread Diameter:	0.875 Inches
Grip Length:	2.250 Inches Nominal
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Special Features:	Centerdrill In Point End At Manufacturer's Option On Dash Number 12 And 14 Sizes
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PBF1593-14-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.