

Description

Fastener Length: 3-43/64", Thread: 1/2-20, Thread Length: 49/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PBF1602C8D46
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-504-1087
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N PBF1602C8D46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.770 Inches Nominal
Fastener Length:	3.645 Inches Minimum And 3.685 Inches Maximum
Head Style:	Hexagon
Head Height:	0.328 Inches Minimum And 0.360 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Shoulder Diameter:	0.620 Inches Minimum First Shoulder And 0.624 Inches Maximum First Shoulder
Shoulder Length:	2.885 Inches Minimum First Shoulder And 2.905 Inches Maximum First Shoulder
End Item Identification:	C-17a Aircraft
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	167 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Part Name Assigned By Controlling Agency:	Bolt,shoulder - Hexagon Head, A286
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall And Vsm 1327 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PBF1602C8D46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.