

# P/N PBF7521-8DN25

Military-Fasteners.com

#### Description

Fastener Length: 2-3/32", Thread: 1/2-20, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	PBF75218DN25
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-060-6843
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N PBF7521-8DN25 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	2.080 Inches Minimum And 2.100 Inches Maximum
Head Style:	Spline Drive Shear Head
-	0.281 Inches Nominal
Head Height:	
Width Between Flats:	0.901 Inches Maximum
Grip Diameter:	0.4982 Inches Minimum And 0.4991 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.552 Inches Minimum And 1.572 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.825 Inches Minimum First Hole And 1.845 Inches Maximum First Hole
Special Features:	Dry Film Lube Per Mil-I-8937b On Bearing Surface Of Head And Grip
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Threads
Surface Treatment:	Cadmium Top Of Head
Surface Treatment Document And Classification:	Nas672 National Spec Single Treatment Response Threads
Surface Treatment Document And Classification:	Nas672 National Spec Single Treatment Response Top Of Head
Thread Series Designator:	Unjf

### How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/PBF7521-8DN25</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.