

Description

Fastener Length: 1/2", Thread: 6-32, Head Width: 3/16", Thread Length: 9/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PC910633
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-331-1250
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N PC91063-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.150 Inches Minimum And 0.155 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
First Diameter From Head:	0.100 Inches Minimum And 0.105 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.315 Inches Minimum And 0.350 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Color:	Black Overall
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Mil-c-13924 Cl 4 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/PC91063-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.