

**Description**

Fastener Length: 1/2", Thread: 6-32, Head Width: 3/16", Thread Length: 9/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	PC910633
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-331-1250
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N PC91063-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.150 Inches Minimum And 0.155 Inches Maximum
<b>Fastener Length:</b>	0.470 Inches Minimum And 0.500 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.218 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.134 Inches Minimum And 0.138 Inches Maximum
<b>First Diameter From Head:</b>	0.100 Inches Minimum And 0.105 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.315 Inches Minimum And 0.350 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Width Across Flats:</b>	0.188 Inches Minimum And 0.190 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Color:</b>	Black Overall
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Oxide Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-13924 Cl 4 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/PC91063-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.