

Description

Fastener Length: 9/32", Head Width: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PLT21463
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-989-7598
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N PLT214-6-3 Specifications

Fastener Length:	0.276 Inches Minimum And 0.306 Inches Maximum
Head Style:	Hexagon
Head Height:	0.103 Inches Minimum And 0.113 Inches Maximum
Shank Diameter:	0.202 Inches Minimum And 0.203 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.156 Inches Minimum And 0.219 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Hardness Rating:	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
Heat Treatment:	Annealed Overall
Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
Material:	Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut
Material:	Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Or Steel Comp 303 Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Ams 5614 Assn Std 2nd Material Response Sleeve Or Astm A582 Assn Std 3rd Material Response Sleeve
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Sleeve And Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PLT214-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.