

Description

Fastener Length: 27/64", Head Width: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PLT21465
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-914-3249
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

# P/N PLT214-6-5 Specifications

Fastener Length:	0.401 Inches Minimum And 0.431 Inches Maximum
Head Style:	Hexagon
Head Height:	0.103 Inches Minimum And 0.113 Inches Maximum
Shank Diameter:	0.202 Inches Minimum And 0.203 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Mandrel
Lubrication:	Wax Or Dry Film
Grip Length:	0.281 Inches Minimum And 0.344 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Shear Strength:	5240 Double Pounds Per Square Inch
Material:	Steel Comp 303f Sleeve
Material:	Steel Comp 4130 Stem Or Steel Comp 8740 Stem Or Steel Comp 4140 Stem
Material:	Steel Comp 4130 Body Or Steel Comp 8740 Body Or Steel Comp 4140 Body
Material Document And Classification:	Ams 5641 Assn Std Single Material Response Sleeve
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Body Or Mil-s-6049 Mil Spec 2nd Material Response Body Or Mil-s-5626 Mil Spec 3rd Material Response Body
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem Or Mil-s-5626 Mil Spec 3rd Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PLT214-6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.