

Description

Fastener Length: 1/2", Head Width: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PLT21467
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-880-5116
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N PLT214-6-7 Specifications

Fastener Length:	0.541 Inches Nominal
Head Style:	Hexagon
Head Height:	0.103 Inches Minimum And 0.113 Inches Maximum
Shank Diameter:	0.203 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Lubrication:	Cetyl Alcohol And Grease Film And Wax
Grip Length:	0.438 Inches Nominal
Width Across Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Material:	Steel Comp 431 Sleeve Or Iron Alloy 660 Sleeve Or Steel Comp 303f Sleeve
Material Document And Classification:	-1l-s-6758 Mil Spec 1st Material Response Bolt Or -1l-s-5626 Mil Spec 2nd Material Response Bolt Or -1l-s-6049 Mil Spec 3rd Material Response Bolt
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Passivate Sleeve And Cadmium Sleeve
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec 1st Treatment Response Sleeve And Qq-p-416 Ty 1 Cl 2 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Nut

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/PLT214-6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.