

Description

PLT251-6-3 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	PLT25163
Minimum Qty (MOQ):	1
NSN:	5320-00-020-6851
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

P/N PLT251-6-3 Specifications

Head Style:	Hexagon
Head Height:	0.113 Inches Maximum
Shank Diameter:	0.213 Inches Minimum And 0.215 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Mandrel
Lubrication:	Cetyl Alcohol
Grip Length:	0.157 Nominal Mills And 0.219 Nominal Centimeters
Width Across Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Hardness Rating:	48.0 Rockwell C Minimum Overall And 55.0 Rockwell C Maximum Overall
Shear Strength:	6900 Double Pounds Per Square Inch
Material:	Iron Alloy 660 Sleeve Or Nickel Alloy X-750 Sleeve
Material:	Steel Comp H11 Body
Material:	Steel Comp H11 Stem
Material Document And Classification:	Ams 5735 Assn Std 1st Material Response Sleeve Or Ams 5582 Assn Std 2nd Material Response Sleeve
Material Document And Classification:	Ams 6487 Assn Std 1st Material Response Body
Material Document And Classification:	Ams 6487 Assn Std 1st Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Stem
Surface Treatment Document And Classification:	Nas672 Assn Std Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/PLT251-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.