

**Description**

Fastener Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	PLT547067
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-373-8754
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N PLT5470-6-7 Specifications

<b>Fastener Length:</b>	0.870 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.1970 Inches Minimum And 0.1990 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.5716 Inches Nominal
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film Or Paraffin Wax Or Cetyl Alcohol
<b>Grip Length:</b>	0.407 Inches Minimum And 0.469 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 Bolttitanium Alloy Uns R56400 Nutsteel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Bolt Or Ams 4967 Assn Std Single Material Response Boltams 4928 Assn Std Single Material Response Nut Or Ams 4967 Assn Std Single Material Response Nut
<b>Surface Treatment:</b>	Passivate Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/PLT5470-6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.