



Military-Fasteners.com

P/N PLT5470-6-8

Description

Fastener Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PLT547068
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-373-8753
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N PLT5470-6-8 Specifications

<b>Fastener Length:</b>	0.932 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.1970 Inches Minimum And 0.1990 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.5716 Inches Nominal
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film Or Paraffin Wax Or Cetyl Alcohol
<b>Grip Length:</b>	0.470 Inches Minimum And 0.531 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 BoltTitanium Alloy Uns R56400 Nutsteel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Nut Or Ams 4967 Assn Std Single Material Response Nut
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/PLT5470-6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.