

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PLT547068
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-373-8753
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N PLT5470-6-8 Specifications

Fastener Length:	0.932 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1970 Inches Minimum And 0.1990 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.5716 Inches Nominal
Expansion Device:	Threaded Stem
Lubrication:	Dry Film Or Paraffin Wax Or Cetyl Alcohol
Grip Length:	0.470 Inches Minimum And 0.531 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 BoltTitanium Alloy Uns R56400 Nutsteel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Nut Or Ams 4967 Assn Std Single Material Response Nut
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/PLT5470-6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.