

Description

Fastener Length: 15/64", Thread: 4-40, Head Width: 1/16", Thread Length: 7/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	PZ13
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-395-4193
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N PZ-1-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.110 Inches Minimum And 0.120 Inches Maximum
Fastener Length:	0.236 Inches Minimum And 0.248 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.250 Inches Nominal
Head Height:	0.125 Inches Nominal
Shoulder Diameter:	0.1235 Inches Minimum First Shoulder And 0.1245 Inches Maximum First Shoulder
Shoulder Length:	0.1255 Inches Minimum First Shoulder And 0.1275 Inches Maximum First Shoulder
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.078 Inches Nominal
Thread Quantity Per Inch:	40
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582, Cond A Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/PZ-1-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.