

Description

Fastener Length: 15/64", Thread: 4-40, Head Width: 1/16", Thread Length: 7/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | PZ13 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-395-4193 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N PZ-1-3 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.110 Inches Minimum And 0.120 Inches Maximum |
| Fastener Length: | 0.236 Inches Minimum And 0.248 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.250 Inches Nominal |
| Head Height: | 0.125 Inches Nominal |
| Shoulder Diameter: | 0.1235 Inches Minimum First Shoulder And 0.1245 Inches Maximum First Shoulder |
| Shoulder Length: | 0.1255 Inches Minimum First Shoulder And 0.1275 Inches Maximum First Shoulder |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.078 Inches Nominal |
| Thread Quantity Per Inch: | 40 |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp 303 Overall |
| Material Document And Classification: | Astm A582, Cond A Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/PZ-1-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.