

Description

Fastener Length: 7/8", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	R134P1SL
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-832-4602
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N R134P1SL Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.621 Inches Minimum And 0.635 Inches Maximum
<b>Fastener Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.250 Inches Minimum And 0.270 Inches Maximum
<b>Width Between Flats:</b>	0.245 Inches Minimum And 0.251 Inches Maximum
<b>Extended Washer Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Extended Washer Thickness:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Hole Diameter:</b>	0.047 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Unfinished Head
<b>Nonstandard Thread Pitch Diameter:</b>	+0.1644/+0.1667 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 33.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Double Hexagon Longitudinal Hole
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Thread Series Designator:</b>	Uns

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/R134P1SL> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.