

Description

Fastener Length: 61/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	S0046538P
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-363-8475
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N S00465-3-8P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.318 Inches Nominal
Fastener Length:	0.933 Inches Minimum And 0.963 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.383 Inches Minimum And 0.390 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty li,cl 2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/S00465-3-8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.