

**Description**

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	S00465412P
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-445-3051
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N S00465-4-12P Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.363 Inches Nominal
<b>Fastener Length:</b>	1.227 Inches Minimum And 1.257 Inches Maximum
<b>Head Diameter:</b>	0.466 Inches Minimum And 0.518 Inches Maximum
<b>Internal Drive Style:</b>	Torque-set Ribbed
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class 2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/S00465-4-12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.