

Description

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	S0046544P
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-436-0791
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N S00465-4-4P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Nominal
Fastener Length:	0.730 Inches Minimum And 0.760 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.509 Inches Minimum And 0.518 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Nutplate Cbore Between Grip And Threads/captive Panel Fastener
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std 1st Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/S00465-4-4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.