

Description

Thread Size: 1/8", Nut Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	S6200
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-435-1063
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N S6-200 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Pan No. 2
Head Diameter:	0.310 Inches Minimum And 0.340 Inches Maximum
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.189 Inches Maximum
Nut Length:	0.547 Inches Minimum And 0.577 Inches Maximum
Err Default:	+0.160/+0.200 Inches
Unable To Decode:	+0.160 To 0.200 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/S6-200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.