

## P/N S8157AU292-090G

## **Description**

Hole Diameter: 1/4", Diameter: 33/64", Thickness: 3/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: S8157AU292090G

Minimum Qty (MOQ): 10 EA

NSN: 5310-01-089-7086

Schedule B: 7318.22.0000

ECCN: 9A991

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,



<sup>\*</sup> See page 2 for technical characteristics

# P/N S8157AU292-090G Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.255 Inches Minimum And 0.260 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.085 Inches Minimum And 0.095 Inches Maximum
Overall Diameter:	0.500 Inches Minimum And 0.520 Inches Maximum
Hardness Rating:	38.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Special Features:	Dry Film Lubrication Ems 242 Ty 1 Cagec 70210
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall

## **How to Order**

Order this washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/flat+washers/58157AU292-090G">https://military-fasteners.com/washers/flat+washers/58157AU292-090G</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.