

P/N S8402BH3A

Description

Fastener Length: 15/32", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: S8402BH3A

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-715-2488

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N S8402BH3A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.469 Inches Nominal
Head Style:	Hexagon
Head Height:	0.141 Inches Nominal
Width Between Flats:	0.377 Inches Nominal
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.063 Inches Nominal
Hole Quantity:	2
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/58402BH3A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.