

P/N S8805SA2-10

Description

Fastener Length: 5/8", Hole Diameter: ", Thread: 2-56, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: S8805SA210

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-246-6393

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N S8805SA2-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.558 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.124 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.055 Inches Minimum And 0.062 Inches Maximum
Hole Diameter:	0.031 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Hexagon Flats
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/S8805SA2-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.