

Description

Fastener Length: 1-1/2", Hole Diameter: 3/64", Thread: 6-32, Thread Length: 1-7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	S8805SA623
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-203-6811
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N S8805SA6-23 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.313 Inches Minimum And 1.437 Inches Maximum
Fastener Length:	1.376 Inches Minimum And 1.500 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.118 Inches Minimum And 0.132 Inches Maximum
Hole Diameter:	0.042 Inches Minimum And 0.047 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Il-s-6050 Mil Spec 10th Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl C Mil Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc
Specification/standard Data:	70210-s8805sa6-23 Manufacturers Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/S8805SA6-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.