

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	S88064404
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-973-1883
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N S8806-440-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.121 Inches Minimum And 0.210 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.200 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,c1 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/S8806-440-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.