

P/N S8806CC1032R9

Description

Fastener Length: 9/16", Thread: 10-32, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: S8806CC1032R9

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-482-1231

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N S8806CC1032R9 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.386 Inches Minimum And 0.490 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303
Screw Material Document And Classification:	Qq-s-763 Cond A Fed Spec 1st Material Response Or Qq-s-764 Cond A Fed Spec 2nd Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this flat hd 100� screw-machine from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/S8806CC1032R9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.